



24 Hole Sliding Aluminum Lockout Hasp:

Model	Description	Material
040.162	Accpet up to 24 padlocks	Aluminum

Material				
<ul style="list-style-type: none"> Anodized aluminum finish for superior corrosion resistance. 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> Keeps equipment inoperative while repairs or adjustments are made. Control cannot be turned on until last worker's padlock is removed from hasp. Offset lockout holes ensure hasp cannot be locked in open position. Raised areas for improved sliding action. Color: Red 	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Operating Temperature: -40°C to 110°C / -40°F to 230°F. 				
Chemical Resistance	<p>All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.</p>			

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.