

Adjustable Safety Ball Valve Lockout:



Model	Description	Material
020.160	Suitable for pipe diameter from 73mm(2 4/5") to 215mm (8 1/2")	Plastic ABS

Material				
<ul style="list-style-type: none"> Made from durable ABS, highly resistant to cracking and abrasion and supports extreme weather temperature conditions. 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> Two halves of the lockout encompass the ball valve handle to secure it from inadvertent activation of the valve handle. Easy operation with adjustable sizes available. Only lock out the valves in OFF position. Suggested to lock together with one piece of padlock and a tagout, to warn the valve is not available for operating. For multiple lockout usage, we can use lockout hasp to extend. Colors : Red. Other colors can be customized 	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Temperature range from -20°C to +90°C 				
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.