

### Universal Handle-On Ball Valve Lockout:



Model	Description
020.220	Suitable for valve diameters 6mm(1/4")to101mm(4")and works on insulated pipes and in close quarters.

Dimensions	Features
<ul style="list-style-type: none"> <li>Accept up to 1 padlock, locking shackle max diameter 8mm.</li> <li>For valve diameters from 1/4in (6mm) to 4in (101mm) on insulated pipes and in close quarters.</li> </ul>	<ul style="list-style-type: none"> <li>Designed to lock out different types of ball valves, clamp tight on handle stop to prevent handle movement.</li> <li>Designed to lock out different types of ball valves, clamp tight on handle stop to prevent handle movement.</li> <li>Can be equipped together with hasps for multiple lockout usage.</li> </ul>
Temperature Range	Material
<ul style="list-style-type: none"> <li>Temperature range from -20°C to +120°C</li> </ul>	<ul style="list-style-type: none"> <li>made from zinc alloy, surface treatment by high temperature spraying,rust proof.</li> </ul>

**NOTE:** Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.