

Aluminium Safety Padlock

Model	Description	Material
010.725	Inner shackle:38mm; diameter:6mm	KA, KD, MK, GMK supported



Material				
<ul style="list-style-type: none"> Steel Shackle, length 1-1/2 in. (38mm), diameter 1/4 in. (6mm), Aluminum body Colors: Red, yellow, green, blue, purple, silver, black, orange. 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> Key retaining feature: When the padlock is open, the key can't be removed unless it's locked. 3 shackle Sizes available: 25mm, 38mm and 76mm. Available with various shackle clearances, 8 stock colors, and options for custom keying (KD, KA, MK, GMK) Lightweight yet rugged with a 6pin cylinder and a reserved paracentric keyway 	Acetone	15-60	Nickel salt solns. (chloride, sulfate)	15-30
	Ammonia soln.	15-30	Petroleum	15-30
	Ammonia soln.	48	Silicone oils	<80
	Fuel, engine: Gasoline (Leaded & Unleaded)	48	Toluene	15-30
	Fuel, Diesel	85	Water (including seawater)	15-30
	Heptane	15-30	Water (including seawater) chlorinated (<0.5mg/l)	80
	Lubrication oil: gear oil	<130	Zinc chloride	15-30
	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	<130		
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Service Temperature: 20° to 175°C (0° to 350°F) 	<ul style="list-style-type: none"> Body size : 39mm*14mm*41mm Shackle clearance: 38mm (1.5") Shackle diameter : 6mm 			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				