

Laminated Safety Padlock:

| Model | Description | Material |
|---------|-----------------------|----------------------------|
| 010.780 | 23mm shackle, dia 6mm | Reinforced laminated steel |
| 010.782 | 38mm shackle, dia 6mm | |
| 010.784 | 63mm shackle, dia 6mm | |



| Material |
|--|
| <ul style="list-style-type: none"> Lock body: laminated steel plates Shackle: Hardened Steel UL Rating - UL 94 – HB (Plastic Components Only) Color (of plastic band) : all colors available |



| Features | Chemical | °C | Chemical | °C |
|---|--|---------|---|--|
| | <ul style="list-style-type: none"> Reinforced laminated steel withstands severe physical abuse, hardened steel shackle resists tampering Individually coated body plates provide superior rust protection & corrosion resistance Features a 5-pin cylinder and a key retaining feature Available in two shackle sizes, 6 stock colors, and options for custom keying (KD, KA, MK, GMK) | Acetone | 15-60 | Nickel salt solns. (chloride, sulfate) |
| Ammonia soln. | | 15-30 | Petroleum | 15-30 |
| Ammonia soln. | | 48 | Silicone oils | <80 |
| Fuel, engine: Gasoline (Leaded & Unleaded) | | 48 | Toluene | 15-30 |
| Fuel, Diesel | | 85 | Water (including seawater) | 15-30 |
| Heptane | | 15-30 | Water (including seawater) chlorinated (<0.5mg/l) | 80 |
| Lubrication oil: gear oil | | <130 | Zinc chloride | 15-30 |
| Lubricating oil: HD engine oils, hydraulic oils, transformer oils | | <130 | | |

| Temperature Range | Dimensions |
|-------------------|------------|
|-------------------|------------|

| |
|--|
| <ul style="list-style-type: none"> Service Temperature: -55°C to 100°C (-70° F to 210° F) |
|--|

| Chemical Resistance |
|---------------------|
|---------------------|

All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.

