



Adjustable butterfly Valve Lockout



Model	Description	Material
020.215	Adjustable angle :15-36.	Nylon PA

Material				
<ul style="list-style-type: none">Made from nylon PA, durable, lightweight thermoplastic material, very high chemical resistant and effectively performed in extreme environments.				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none">Adjustable butterfly Valve LockoutLock valves out in seconds by feeding cable lockout device 030.102 through the desired eyelet and around the valve neck to secure the valve from being operated.Directional application arrows allow for ease of installation and minimize user error.Stainless steel rivet allows device to smoothly pivot open and closed to ensure proper fit.	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none">Temprature range from -20°C to +120°C				
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.