



### Adjustable butterfly Valve Lockout



Model	Description	Material
020.242	Lockout Device with 2 Arms	Industrial grade steel and nylon

Material				
<ul style="list-style-type: none"> <li>Made from industrial grade Steel And Nylon, Rugged, easy to use and lightweight.</li> </ul>				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> <li>Enables locking out valves of different types and sizes, such as large levers of valves, T-handles, and other hard-to-secure mechanical devices, with the added stability of 2 arms.</li> <li>No other device offers such flexibility and security</li> <li>Designed to handle extra impact and resist chemicals, making them ideal for just about any environment.</li> </ul>	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"> <li>Temperature range from -20°C to +120°C</li> </ul>	 <ul style="list-style-type: none"> <li>Length: 350mm</li> <li>Height: 180mm</li> <li>Width: 40mm</li> </ul>			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.