

All Purpose Cable Lockout

Model	Description	Material
030.118	Cable diameter 3.8mm, length 2 m	Nylon PA



Material				
<ul style="list-style-type: none"><li>Lock body: made from nylon, with an insulation plastic coated steel cable.</li></ul>				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"><li>Lock body: made from nylon, with an insulation plastic coated steel cable.</li><li>Lock body: made from nylon, with an insulation plastic coated steel cable.</li><li>Lock body: made from nylon, with an insulation plastic coated steel cable.</li></ul>	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"><li>Withstand extra temperatures of -46 degree to 149 degree °C</li></ul>	Cable diameter 3.8mm, length 2 m			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				