

Ball Valve Lockout:

Model	Description	Material
020.172	Hole diameter: 9.8mm	Hardened steel



Material				
<ul style="list-style-type: none"> Made from hardened steel, surface treatment by high-temperature spraying, rust proof. 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> The single-piece design locks can quarter-turn ball valves in the off position. Used on ball valve sizes from 6.35mm (1/4") to 25mm (1"), hole diameter is 3/8". Easy to use, single-piece design locks quarter-turn ball valves in the OFF position Compact size can easily be stored or carried 	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Temperature range from -35°C to +175°C 	<ul style="list-style-type: none"> size : 155mm x 110mm hole diameter: 9.8mm 			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.