



Blocking Arm For Universal Valve Lockout:

Model	Description	Material
020.252	Normal Arm 195mm (L)	Industrial grade steel and nylon



Material				
<ul style="list-style-type: none">Made of industrial-grade steel and nylon for extra impact and chemical resistance.				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none">A versatile, lightweight, and rugged device is easy to use and can lock out numerous types of valves!Can be used to lock out large levers, T-handles and other hard to secure mechanical devices with cable and arm attachments	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none">Glass-filled Nylon: -20° to 120°C (0° to 250°F)	Normal Arm , size : 197mm length			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.