


Car Seal Lockout

Model	Description	Material
030.134	Steel Lockout Cable 1.8mm Diameter, 256mm Length	Aluminum alloy body, with galvanized steel cable
030.136	Nylon Lockout Cable 1.8mm Diameter, 256mm Length	Aluminum alloy body, with nylon cable



Material				
<ul style="list-style-type: none"> Made from durable aluminum alloy body, with galvanized steel cable (030.134) or nylon cable (030.136). 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> Ideal for long-term use, each car seal is self-locking; removal requires cutting the cable after it passes through the body Laser-printed with individual numbering for security and traceability Cable length can be customized Available in red, yellow, green, and blue (standard color for these models: yellow). 	Acetone	60	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Temperature range from -20°C to +90°C 	<ul style="list-style-type: none"> 030.134: Cable diameter 1.8mm, length 256mm 030.136: Cable diameter 1.8mm, length 256mm 			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.