



Steel Cable Shackle Safety Padlock

Model	Description	Lock Shackle material	Specification
010.140.01	Keyed Differ	Steel	“KA”: Each padlock is keyed the same in one group “P”: Straight edge plastic lock body “S”: Steel shackle Other material can be customized: “SS”: Stainless steel shackle “BS”: Brass shackle
010.140.02	Keyed Alike		
010.140.03	Keyed Difer & Master Key		
010.140.04	Keyed Alike & Master Key		
010.140.05	Grand Master Key		



Material				
<ul style="list-style-type: none"> The body is made of reinforced nylon PA66 Shackle made of steel, highly resist of extreme weather and it's non-conductive. 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> 3.2mm Lock shackle the cable shackle is made from stainless steel, ensuring strength and can't be deformed easily. Key retaining: when the shackle is open, the key can not be removed 11 Colors as regular stocks: Red, yellow, green, orange, purple, black, white, brown, grey, blue, dark blue, etc. 	Acetone	15-60	Nickel salt solns. (chloride, sulfate)	15-30
	Ammonia soln.	15-30	Petroleum	15-30
	Ammonia soln.	48	Silicone oils	<80
	Fuel, engine: Gasoline (Leaded & Unleaded)	48	Toluene	15-30
	Fuel, Diesel	85	Water (including seawater)	15-30
	Heptane	15-30	Water (including seawater) chlorinated (<0.5mg/l)	80
	Lubrication oil: gear oil	<130	Zinc chloride	15-30
	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	<130		
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Nylon body withstand temperature from -20°C to +80°C 	<ul style="list-style-type: none"> Body size: Body size: 37mm*45mm*20mm Shackle size : 175mm*6mm*3.2mm 			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				