



Transparent Gate Valve Lockout:

Model	Description	Material
020.180	1" - 2.5" (25mm-64mm)	Plastic ABS
020.182	2.5"-5" (64mm-127mm)	
020.184	5"-6.5" (127mm-165mm)	
020.186	6.5"-10" (165mm-254mm)	
020.190	10"-13" (254mm-330mm)	



Material																												
<ul style="list-style-type: none">Made from durable ABS																												
Features	Chemical	°C	Chemical	°C																								
<ul style="list-style-type: none">Cover the valve handle with the gate valve lockout device and apply a personal padlock and lockout tag to ensure employee safetyTransparent gate valve covers allow visual inspection of the valve position and condition without having to remove the lockout deviceAccepts padlock shackles up to 3/8 in. in diameter	Acetone	25	Petroleum	25																								
	Acetone	60	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120																								
	Fuel, engine: Gasoline (normal & premium grade)	85																										
	Lubrication oil: gear oil	< 120	Water (including seawater)	25																								
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80																								
Temperature Range	Dimensions																											
<ul style="list-style-type: none">Temprature range from -20°C to +90°C																												
Chemical Resistance	<table><tr><th>Part No.</th><th>A</th><th>B</th><th>C</th></tr><tr><td>020.120</td><td>80</td><td>30</td><td>20</td></tr><tr><td>020.122</td><td>142</td><td>27</td><td>45</td></tr><tr><td>020.124</td><td>184</td><td>44</td><td>63</td></tr><tr><td>020.126</td><td>280</td><td>67</td><td>105</td></tr><tr><td>020.128</td><td>364</td><td>67</td><td>105</td></tr></table>				Part No.	A	B	C	020.120	80	30	20	020.122	142	27	45	020.124	184	44	63	020.126	280	67	105	020.128	364	67	105
Part No.	A	B	C																									
020.120	80	30	20																									
020.122	142	27	45																									
020.124	184	44	63																									
020.126	280	67	105																									
020.128	364	67	105																									
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.																												

NOTE: Please note that the values presented in this document are averages and are not intended to be used for specification purposes. The test data and results contained herein are provided for general information only and should not be relied upon by our customers for designing and specifying products or meeting specific performance criteria. We encourage customers who wish to establish specifications or performance criteria for particular product applications to contact us for further information and assistance.