

Ultimate Cable Lockout:



Model	Description	Material
030.120	Cable diameter 1.5mm, length 2m	Durable ABS

Material				
<ul style="list-style-type: none"> Made from durable ABS, with stainless steel cable stored internally, anti-corrosive and temperature-resistant. 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> Push button self-winding mechanism retracts automatically to tightly cinch the cable, leaving no slack. Push button self-winding mechanism retracts automatically to tightly cinch the cable, leaving no slack. Accepts up to 8 padlocks for multiple lockout application, locking shackle max diameter 8mm. Designed to effectively lock out different types of disconnect switches and small gate valves. 	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Glass-filled nylon: -20° to 120°C (0° to 250°F) 	Cable diameter 1.5mm, length 2 m 			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				