

Ultimate Cable Lockout:

Model	Description	Material
030.121	Cable length:1.8mm ,cable diameter:4mm&6mm	Steel + PA



Material				
<ul style="list-style-type: none"> Made from impact resistant engineering plastic PC, other colors can be customized Used 1.8meter stainless steel cable, the outer layer of cable is made from anti-UV PVC (diameter 6.0mm) 				
Features	Chemical	°C	Chemical	°C
<ul style="list-style-type: none"> Tough and flexible nylon core cable Built-in Cable Management System with take-up reel and internal ratcheting mechanism Tension can be increased on the cable even after safety padlocks are applied Contoured thermoplastic cable housing that withstands harsh environments Lightweight thermoplastic body that withstands chemicals Ergonomic design that eases operation even when wearing gloves. 	Acetone	25	Petroleum	25
	Acetone	60	Turpentine oil	25
	Chlorine, chlorine water	25	Turpentine substitute (white spirit)	25
	Fuel, engine: Gasoline (normal & premium grade)	85	Trichloroethane 1,1,1	45
	Lubrication oil: gear oil	< 120	Lubricating oil: HD engine oils, hydraulic oils, transformer oils	< 120
	Fuel, engine: M15 mixture (15% methanol)	70	Water (including seawater)	25
	Methanol	25	Water (including seawater), chlorinated (<0.5mg/l)	80
Temperature Range	Dimensions			
<ul style="list-style-type: none"> Withstand extra temperatures of -46 degree to 149 degree °C 	<ul style="list-style-type: none"> cable diameter:4mm&6mm Locked with 4 padlocks lock shackle diameter is less than 7mm 			
Chemical Resistance				
All approved chemicals listed are based on the manufactures specified chemical resistance chart for plastic material only.				